CR90

CRATE

90L

Peli CRATE is a fully configurable ecosystem built to load, secure, and deploy your equipment with absolute confidence. Engineered from our legendary Peli Protector HPXC resin, CRATE delivers uncompromising, IP67-rated protection against water, dust, and impact. Take control of your exterior with the integrated ModRail™ system of tie-downs, mounts and accessories to securely anchor your loadout to roof racks and truck beds. A multi-position removable lid and interlocking design enable steadfast stacking and instant access to your gear when it matters most. Rugged, stackable, and field-ready, CRATE lets you load, secure, and deploy your equipment anywhere your adventure takes you.



- Limited Lifetime Warranty (Where applicable by law)
- Automatic Pressure Equalization Valve
- Padlockable Hasps
- IP67-rated: waterproof, dustproof, and crushproof performance
- Integrated ModRail™ system for mounts, tie-downs, and modular accessories
- Multi-position, removable lid opens from either side for quick access
- Interlocks securely across multiple sizes for stable stacking
- Reinforced grab handles

CONFIGURATIONS



CR90
Standard



CR90BDL
Case + Organization Kit



CR90
Empty

DIMENSIONS

Interior (L×W×D)	29.00 x 17.00" x 11.00 (73.7 x 43.2 x 27.9 cm)
Exterior (L×W×D)	32.20 x 20.20" x 12.10 (81.8 x 51.3 x 30.7 cm)
Lid Depth	1.69" (4.3 cm)
Bottom Depth	9.31" (23.6 cm)
Total Depth	11" (27.9 cm)
Int Volume	3.14 ft³ (0.089 m³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	Nylon
O-Ring	Silicone
Pins	Aluminum & Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

Black

Desert Tan


WEIGHT

Weight Empty	17.50 lbs (7.94 kg)
Master Pack Weight	21.30 lbs (9.66 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)


ACCESSORIES



TRAY90
CRATE 90L Inner Tray



DIVID90
CRATE 90L Divider Panel Set



MOLPANL
CRATE EZ-Click MOLLE Lid Panel

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 11-17-26