

SOLO BEAM

PWL0120 / PWL0121

APPLICATIONS: AUTOMOTIVE SERVICES, DETAILING, WORK SAFETY, INDUSTRIAL, DIY

✱ 5000 lm

◀ 85 m

POWER SUPPLY	Power Tool Battery 18V 5000 mAh / Li-Ion 14,8V 5200 mAh		
CHARGING TIME	4 h 30 min (Li-Ion 14,8V 5200 mAh)		
	LIGHT OUTPUT	RUN TIME	BEAM DISTANCE
	Power Tool Battery 18V 5000 mAh		
HIGH	5000 lm	2 h 15 min	85 m
MEDIUM	2500 lm	4 h 30 min	-
LOW	1500 lm	7 h 15 min	-
SURVIVAL	500 lm	20 h	-
	Li-Ion 14,8V 5200 mAh		
HIGH	5000 lm	2 h	85 m
MEDIUM	2500 lm	4 h	-
LOW	1500 lm	6 h	-
SURVIVAL	500 lm	15 h	-
DIMENSIONS	280 x 280 x 148 mm		
WEIGHT	1,98 kg (without battery); 2,63 kg (with battery & adapter)		
THE SET INCLUDES	PWL0120: Li-Ion battery, Mactronic Li-Ion battery adapter, 4 x Power Tool Battery Adapters (Milwaukee®, Makita®, Bosch® Professional, DeWalt®) PWL0121: Mactronic Li-Ion battery adapter, 4 x Power Tool Battery Adapters (Milwaukee®, Makita®, Bosch® Professional, DeWalt®)		



IP65
RATING



IK10
RATING



BATTERY LEVEL
INDICATOR



CONTROL
PANEL



ADJUSTABLE
HEAD



HOOKS



MAGNET



2700 K / 3500 K / 4500 K
5500 K / 6500 K

Solo Beam is a compact work light designed for service, installation, workshop, and field applications. It can be powered by a Mactronic Li-Ion 14.8 V 5200 mAh battery or by 18–20 V batteries from leading power tool brands. It delivers up to 5000 lm, provides a beam distance of up to 85 m, and allows color temperature adjustment from 2700 to 6500 K in every lighting mode. The rear control panel, adjustable stand, and hanging hooks make it easy to use in a wide range of conditions, while the IP65 and IK10 ratings confirm its durability. Two versions are available: with adapters, battery, and charger (PWL0120), or with adapters only (PWL0121). An optional magnetic mount, sold separately, allows convenient attachment to metal surfaces.

PRODUCT MEETS THE FOLLOWING STANDARDS:



MACTRONIC®
VALUE
HIGHLIGHTS

5-YEAR
WARRANTY

PATENTED
DESIGN

ECO FRIENDLY
PACKAGING

SCAN ME

