

GALAXY 3.1 BLACK

RDL0112-2B

APPLICATIONS: MILITARY, AIR DEFENSE, MEDICAL, RESCUE

✱ 4500 lm



POWER SUPPLY	230V AC / 50 Hz
POWER	8W - 30W
LIGHT OUTPUT	1200 lm - 4500 lm
OPERATING TEMPERATURE	-35° C - +50° C
COLOR TEMPERATURE	4000 K
LIFESPAN	80 000 h
HOUSING	aluminum, polycarbonate
DIMENSIONS	350 x 103 x 100 mm (+ cord with power switch 450 mm)
WEIGHT	1,70 kg
THE SET INCLUDES	RDL0112-2B: Shelter Light, Mounting Accessories: 2 x hanging wire ropes, 2 x straps with carabiners - > up to 15 units in series
OUT OF SET	RDL0112-P5B: 5 m Power Cord with IP54 Schuko plug (sold separately) RDL0013-P5B: 5 m Power Cord with IP68 BALS Schuko plug (sold separately) RDL0010-P2.5-2B: 2.5 m Interconnection Cord (sold separately)



Galaxy 3.1 Black is a professional shelter light engineered for industrial, rescue, medical, and military applications. The new black-housing version features the Advanced Dimming System (ADS), offering smooth brightness control from 1200 lm to 4500 lm for precise adjustment to task requirements and operating conditions. The system supports a linear connection of up to 15 lights within a single power circuit. Its IP66- and IK10-rated housing provides protection against dust, water, and mechanical damage. The set includes only mounting accessories: 2 steel hanging wire ropes and 2 straps with carabiners. Power cords are available separately (with an IP54 Schuko plug or an IP68 BALS Schuko plug).

PRODUCT MEETS THE FOLLOWING STANDARDS:

MACTRONIC®
VALUE
HIGHLIGHTS

5-YEAR
WARRANTY

PATENTED
DESIGN

ECO FRIENDLY
PACKAGING

