

TOWER BEAM X3

PFL0320

APPLICATIONS: INDUSTRIAL, CONSTRUCTION, LAW ENFORCEMENT, UNIFORMED SERVICES, RESCUE, WORK SAFETY, ROADWORKS, UTILITIES

POWER SUPPLY	230V AC / Power Tool Battery (Li-Ion 18V, 5A)		
POWER	80 W		
CHARGING TIME	8 h (5 Ah, 18V, 5A)		
	LIGHT OUTPUT	RUN TIME	BEAM DISTANCE
Power Tool Battery 18V, 5000 mAh			
BOOST	10 000 lm	1 h 30 min	120 m
HIGH	8000 lm	2 h	108 m
MEDIUM	6000 lm	2 h 45 min	95 m
LOW	4000 lm	4 h	76 m
SURVIVAL	2000 lm	8 h	55 m
AC 230V			
BOOST	6000 lm	-	90 m
HIGH	4800 lm	-	80 m
MEDIUM	3500 lm	-	72 m
LOW	2200 lm	-	59 m
SURVIVAL	1000 lm	-	42 m
DIMENSIONS	1100 x 199 x 207 mm		
WEIGHT	8 kg (without battery)		
THE SET INCLUDES	230V AC Power Adapter, 5 x Power Tool Battery Adapters* (Milwaukee®, Makita®, Bosch® Professional, Bosch® (Home & Garden), DeWalt®), anchor pins (10 pcs.), HD transport bag. BATTERIES ARE NOT INCLUDED		

- IPX4 RATING
- IK07 RATING
- 1 m IMPACT RESISTANCE
- HYBRID POWER MODE
- ADJUSTABLE HEADS
- POWER BANK
- CONTROL PANEL
- BATTERY LEVEL INDICATOR

✱ 10 000 lm

◀ 120 m



5 adapters, without batteries



Tower Beam X3 is a professional-grade area light designed for industrial, service, and rescue applications. Hybrid Power Mode allows it to be powered from 230 V AC mains or from 18 V / 5 Ah power-tool batteries, with five adapters included for Milwaukee®, Makita®, Bosch® Professional, Bosch® Home & Garden, and DeWalt®. Three adjustable heads provide 360° all-around illumination and precise beam positioning. On battery power, it delivers light output up to 10 000 lm, while on AC power it provides up to 6000 lm. Control via the integrated panel, a battery level indicator, and USB-A and USB-C ports with power bank function make field operation easier. The choice of 4000 K or 6500 K color temperature, combined with CRI 80, provides good visibility and natural color rendering. An operating temperature range of -20 to +40°C ensures reliable performance in changing conditions.

*All product names, logos, and brands are property of their respective owners. Milwaukee®, Makita®, Bosch®, and DeWalt® are registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. These battery adapters are manufactured by Mactronic® and are designed for compatibility with the specified battery systems only.

PRODUCT MEETS THE FOLLOWING STANDARDS: CE RoHS

MACTRONIC®
VALUE
HIGHLIGHTS

5-YEAR
WARRANTY

PATENTED
DESIGN

ECO FRIENDLY
PACKAGING

