

TOWER BEAM X2

PFL0330

APPLICATIONS: INDUSTRIAL, CONSTRUCTION, LAW ENFORCEMENT, UNIFORMED SERVICES, RESCUE, WORK SAFETY, ROADWORKS, UTILITIES

POWER SUPPLY	AC 230V / 2 x Li-Ion 25,6V 3,8 Ah		
CHARGING TIME	5 h 15 min (2 x bat.), 2 h 50 min (1 x bat.)		
	LIGHT OUTPUT	RUN TIME	BEAM DISTANCE
AC 230V			
ADS	0-14 000 lm	-	-
2 x Li-Ion 25,6V 3800 mAh			
BOOST	8000 lm	6 h 30 min	356 m
HIGH	5000 lm	13 h 10 min	287 m
MEDIUM	3000 lm	26 h 15 min	240 m
LOW	800 lm	71 h 30 min	88 m
DIMENSIONS	1250 x 261 x 200 mm		
WEIGHT	8,2 kg (without battery), 10 kg (with battery)		
THE SET INCLUDES	230V AC charger, 230V AC driver, 2 x Li-Ion 25.6V, 3.8 Ah, anchor pins (10 pcs.), HD transport bag		

✱ 14 000 lm

◀ 356 m



- IP66 RATING

IK10 RATING

ADVANCED DIMMING SYSTEM

HYBRID POWER MODE
- ADJUSTABLE HEADS

POWER BANK

CONTROL PANEL

BATTERY LEVEL INDICATOR



Tower Beam X2 is a high-performance area light designed for industrial, service, emergency response, and rescue applications. With Hybrid Power Mode, it can run on 230V AC or two 25.6V 3.8Ah Li-Ion batteries. It delivers up to 8000 lm on batteries and up to 14 000 lm when connected to AC power and used with ADS. The adjustable mast extends to 3.1 m, while two adjustable heads help illuminate a larger work area effectively. Run time reaches up to 3 days in Low mode. A Power Bank function, dual charger included, and compact folded form make it easy to transport, deploy quickly, and use efficiently on site, in the field, and during blackouts or emergency situations.

PRODUCT MEETS THE FOLLOWING STANDARDS:

CE

RoHS

MACTRONIC®
 VALUE
 HIGHLIGHTS

5-YEAR
 WARRANTY

PATENTED
 DESIGN

ECO FRIENDLY
 PACKAGING

