

M-FIRE GUARDIAN XW

PHH0235/PHH0236/PHH0238

APPLICATIONS: FIREFIGHTING, RESCUE, WORK SAFETY, INDUSTRIAL, OIL & GAS, CHEMICALS

ANSI FL1 STANDARD

240 lm

205 m

POWER SUPPLY	Li-Ion 3.6V 2600 mAh rechargeable battery			
CHARGING TIME	4 h			
	LIGHT OUTPUT	RUN TIME	BEAM DISTANCE	PEAK BEAM INTENSITY
SPOT HIGH	240 lm	6 h	205 m	10 350 cd
SPOT MEDIUM	120 lm	12 h 20 min	145 m	5150 cd
SPOT LOW	70 lm	20 h 45 min	115 m	3170 cd
SPOT ECO	6 lm	224 h	33 m	280 cd
SPOT FLASHING	-	12 h 15 min	-	-
FLOOD CONSTANT	25 lm	50 h	10 m	22 cd
FLOOD FLASHING	-	80 h	-	-
SPOT + FLOOD	240 lm	5 h 30 min	-	-
DIMENSIONS	177 x 64 x 67 mm			
WEIGHT	305 g			
THE SET INCLUDES	PHH0235: charging base, 230V AC charger, 12V DC car charger PHH0236: charging base, 12V DC car charger PHH0238: flashlight only			



I M1 Ex ia I Ma
II 1G Ex ia IIC T4 Ga
CSANe 22ATEX1206X



M-Fire Guardian XW is a rechargeable right angle flashlight with ATEX certification for safe use in explosive atmospheres. It features two light beams: a focused main beam of up to 240 lm and a beam distance of up to 205 m, perfect for penetrating smoke, and a 25 lm wide auxiliary beam for broader area illumination, ideal for spatial orientation. Powered by a 2600 mAh Li-Ion battery, it provides up to 6 hours of operation in High mode and up to 80 hours with the auxiliary beam. Its rugged IP67-rated body ensures durability in the most demanding environments.

PRODUCT MEETS THE FOLLOWING STANDARDS: CE RoHS

MACTRONIC®
VALUE
HIGHLIGHTS

5-YEAR
WARRANTY

PATENTED
DESIGN

ECO FRIENDLY
PACKAGING

SCAN ME

