

M-FIRE 03 HL

PHH0215

APPLICATIONS: FIREFIGHTING, RESCUE, WORK SAFETY, INDUSTRIAL, OIL & GAS, CHEMICALS

ANSI FL1 STANDARD

✱ 400 lm

◀ 150 m

POWER SUPPLY	4 x AA			
	LIGHT OUTPUT	RUN TIME	BEAM DISTANCE	PEAK BEAM INTENSITY
HIGH	400 lm	8 h 10 min	150 m	5660 cd
LOW	145 lm	13 h 10 min	90 m	1975 cd
DIMENSIONS	172 x 47 x 47 mm			
WEIGHT	140 g (without batteries), 270 g (with batteries)			
THE SET INCLUDES	4 x AA batteries, clip			

ADDITIONAL ACCESORIES:

RHH0051	Rosenbauer Heroes Titan mount
PHH0012M-UP	Gallet helmet mount
RHH0041	Calisia helmet mount
T-MX142-NAKLADKA-CZ	Signal cone, red
T-MX142-NAKLADKA-Z	Signal cone, yellow
T-PHH0215-CONE-R	Signal cone, red



NEW



M-Fire 03 HL flashlight, with ATEX certification, is designed for safe use in explosion-hazard areas. It combines safety with performance and is suitable for zones with highly explosive gases like hydrogen and acetylene (IIC classification). With 400 lumens and a beam distance of 150 meters, the M-Fire 03 HL delivers powerful illumination, even in harsh conditions. Its IPX7 protection ensures water resistance up to 1 meter for 30 minutes. Powered by four AA batteries, it offers a reliable and easily replaceable power source without needing specialized chargers. The flashlight includes a clip for attachment to clothing or gear and can be mounted on firefighter helmets or paired with a traffic control cone for added versatility.

PRODUCT MEETS THE FOLLOWING STANDARDS:   

MACTRONIC®
VALUE
HIGHLIGHTS

5-YEAR
WARRANTY


PATENTED
DESIGN


ECO FRIENDLY
PACKAGING

SCAN ME

