

TOWER BEAM

PFLD300

APPLICATIONS: INDUSTRIAL, CONSTRUCTION, LAW ENFORCEMENT, UNIFORMED SERVICES, RESCUE, WORK SAFETY, ROADWORKS, UTILITIES

POWER SUPPLY	AC 230V / Li-Ion 24,5V, 4 Ah		
POWER	79,2 W		
CHARGING TIME	3 h 40 min		
	LIGHT OUTPUT	RUN TIME	BEAM DISTANCE
AC 230V			
ADS	0-12 000 lm	-	-
Li-Ion 24,5V, 4 Ah			
BOOST	6000 lm	4 h	222 m
HIGH	3500 lm	8 h	154 m
MEDIUM	2200 lm	20 h	121 m
LOW	600 lm	45 h	65 m
DIMENSIONS	1070 x 240 x 300 mm		
WEIGHT	6,3 kg		
THE SET INCLUDES	Li-Ion battery, 230V AC charger, 230V AC driver, anchor pins (10 pcs.), HD transport bag		

✱ 12 000 lm

◀ 40 m



- IP66 RATING
- POWER BANK
- HYBRID POWER MODE
- BATTERY LEVEL INDICATOR
- CONTROL PANEL
- ADVANCED DIMMING SYSTEM
- ADJUSTABLE HEADS



Tower Beam is a portable, battery-powered lighting system for industrial, rescue, and inspection applications. It features two rotatable heads on an adjustable tripod with a height of up to 2.3 m, offering four operating modes and a beam distance of 40 m in Boost mode. The Hybrid Power Mode allows power from the mains (230V) or a replaceable Li-Ion 24,5V 4Ah battery, which charges in 3 h and 40 m. The Advanced Dimming System allows smooth, light intensity adjustment from 0 to 12,000 lm. The system has an IP66. It includes hanging hooks, a phone stand, and two USB ports with a power bank function. The set has a Li-Ion battery, 230V AC charger, 230V AC driver, anchor pins, and an HD transport bag.

PRODUCT MEETS THE FOLLOWING STANDARDS:   

MACTRONIC®
VALUE
HIGHLIGHTS

5-YEAR
WARRANTY

PATENTED
DESIGN

ECO FRIENDLY
PACKAGING

SCAN ME

