

M-FIRE AG Ex

PHH0221

APPLICATIONS: FIREFIGHTING, RESCUE, WORK SAFETY, INDUSTRIAL, OIL & GAS, CHEMICALS

|                  |                                                   |            |               |                     |
|------------------|---------------------------------------------------|------------|---------------|---------------------|
| POWER SUPPLY     | 4 × AA                                            |            |               |                     |
|                  | LIGHT OUTPUT                                      | RUN TIME   | BEAM DISTANCE | PEAK BEAM INTENSITY |
| HIGH             | 323 lm                                            | 6 h 30 min | 288 m         | 20 788 cd           |
| MEDIUM           | 140 lm                                            | 13 h       | 184 m         | 8524 cd             |
| DIMENSIONS       | 183 × 63 × 69 mm                                  |            |               |                     |
| WEIGHT           | 250 g (without batteries), 354 g (with batteries) |            |               |                     |
| THE SET INCLUDES | 4 × AA batteries, clip, mount                     |            |               |                     |

ADDITIONAL ACCESORIES:

|           |                                         |
|-----------|-----------------------------------------|
| PHH0021H2 | Wall mounting bracket for 2 flashlights |
|-----------|-----------------------------------------|



I M1 Ex ia I Ma  
II 1G Ex ia IIC T4 Ga  
Sira 15ATEX2166X

ANSI FL1 STANDARD

✱ 323 lm

◀ 288 m



M-Fire AG Ex is an ATEX-certified angle flashlight designed for explosion-hazard zones [Zone 0]. Its intrinsically safe design ensures it is safely operated in high-risk environments prone to ignition, such as industrial fires or emergencies in explosive atmospheres. Emitting a 323-lumen light output with a beam distance of up to 288 meters provides exceptional visibility even in dense smoke. Powered by 4 AA batteries, it offers prolonged operation, making it reliable in critical situations. The IP54 protection rating shields the flashlight from dust and water splashes, while the ergonomic clip allows easy attachment to gear, making it an essential tool during rescue operations.

PRODUCT MEETS THE FOLLOWING STANDARDS:



MACTRONIC®  
VALUE  
HIGHLIGHTS

5-YEAR  
WARRANTY

PATENTED  
DESIGN

ECO FRIENDLY  
PACKAGING

SCAN ME

