

BLACK EYE MINI

THH0082
APPLICATIONS: EDC, OUTDOOR, MILITARY, INDUSTRIAL

ANSI FL1 STANDARD
550 lm
283 m

POWER SUPPLY	14500 Li-Ion 3.7V 750 mAh / 1 x AA			
CHARGING TIME	3-4 h			
	LIGHT OUTPUT	RUN TIME	BEAM DISTANCE	PEAK BEAM INTENSITY
FLOOD HIGH	550 lm	1 h	46 m	533 cd
FLOOD MEDIUM	168 lm	2 h 40 min	24 m	140 cd
FLOOD LOW	10 lm	24 h	6 m	9 cd
FLOOD STROBE	550 lm	2 h 20 min	-	-
SPOT HIGH	172 lm	1 h	283 m	20 009 cd
SPOT MEDIUM	46 lm	2 h 40 min	154 m	5917 cd
SPOT LOW	3,5 lm	24 h	39 m	381 cd
SPOT STROBE	172 lm	20 h 20 min	-	-
DIMENSIONS	104 x 22 x 26 mm			
WEIGHT	51,7 g (without battery); 71,2 g (with battery)			
THE SET INCLUDES	14500 Li-Ion 3.7V 750 mAh Rechargeable Battery, USB-C Cord, Handstrap, Clip			



Black Eye Mini is a compact handheld flashlight with a Focus function and Dual Source System (DSS), built for everyday carry, service work, inspections, outdoor use, and uniformed-service operations. Smooth beam adjustment lets users move from a wide work light to a focused beam with a beam distance of up to 283 m. With up to 550 lm, Last Setting Memory, and a tailcap tactical switch, it is easy to operate with one hand. DSS lets the flashlight run on either a 14500 Li-Ion 3.7 V 750 mAh rechargeable battery or an AA battery. USB-C charging works through the flashlight or directly through the battery, and the indicator near the head shows the battery level. IPX4 rating, 1 m impact resistance, a clip, and a handstrap support reliable field use.

PRODUCT MEETS THE FOLLOWING STANDARDS:   

MACTRONIC® VALUE HIGHLIGHTS

5-YEAR WARRANTY

PATENTED DESIGN

ECO FRIENDLY PACKAGING

SCAN ME
